

Specification Sheet

Model # SA-37W-BVS2

The Solaro Basement Ventilation System helps keep your home safe for family, friends and pets by reducing moisture and harmful gas build-up (such as radon). And keeping fresh air circulating for a clean, energized feeling. The Solaro BVS2 comes with a DC power supply to plug right into your home, but a 37W - solar powered kit is also available. All units also include a timer that can be used on DC (house) power and manually set to run your unit at maximum energy efficiency



kick on to the air for freshness. **Technical Information**

Weight

Fan Weight: 56 lbs / 25.4 kg

NOTE: Total KIT weight could vary

Performance

to maintain a safe and healthy radon level or to periodically

Air Flow Rate: 900 to 1200 CFM Depending on solar exposure Ventilation: Up to 1600 sq.ft.

Electrical

Solar Panel: 37 watt, 17 to 22 DC, 1.5 amp, 36 mono-crystalline cell, solar cells with black back

Motor: Solaro Max Aire Brushless DC Motor, 10-22VDC DC ONLY 110W

6' reach with provided power cord Use **ONLY** with Provided Power Supply

Material

Housing System: Spun Formed, Aircraft Grade Aluminum

Fan Blade: 12" Aluminum, Factory Balanced

Wiring: 18 Gauge Copper Conductors with PVC Insulation

ActiveAire

Housing & Flashing System

Aircraft grade, aluminum for the utmost quality and protection

Inner housing system is aerodynamically designed to produce the highest possible radial air exhaust

Powder coated outer shell

Brushless Electronic Motor with Maximum Yield Technology. This new motor technology was developed by Solaro Energy - Our engineers leveraged lessons learned from our original brushless electronic motor that we used for over 12 years. This new motor technology offers about 30% better efficiency and air moving performance, with an amazing 100,000 hours average motor run time!

Max Aire Motor

Fan Blades

Specifically designed for the Solaro Aire solar powered ventilation system

12" - 5 blade aluminum fan, aerodynamically optimized blade to improve airflow Operates whisper quiet throughout the day



Components

Timer

Allows on/off cycle to be set in 30 minute intervals

Easy to Set and Change



6" Flex Ducting and 6" Vents

1 - 10' long / 6" Flex Ducting (Flex ducting to be cut in half) 2 - 6" vents



Solar Panel

37 watt, 1.5 amp proprietary, high purity, solar panel Weather proof in the most severe conditions High transparent, low iron tempered glass

Wire: 25' Cable 18 Gauge stranded copper

Dimensions

Maintenance: Simple exterior cleaning with soap and water. Dry with soft cloth



Important Note: The Solaro Basement Ventilation System is 100% fire proof and all electrical components are hidden under the air diverting cowling creating an extremely safe and efficient ventilation system Limited Lifetime Warranty - See warranty details for additional information.

888-355-5786



solaroenergy.com

22955 McAuliffe Drive, Suite A • Robertsdale, AL 65767