Specification Sheet Model # SD-70W-SL

SOI A RO



The Solaro Street Light integrates the green-energy solar panel, LED lamp and the lithium battery into a single product. This product is meant to be placed in your garden, residential area, courtyard, road, main area, parking area, parking area or provide light on roads where it is necessary. The battery provides the necessary energy for lighting. And the solar panel to charges the battery.

Technical Information

Specs. Packaged Weight: 42 lbs / 18.16 kg

Warranty: 1 Year

Mounting Height: 5 - 6m

Performance Lumen: 4100 - 4300 lumens 2700-7000K LED: 42 pcs, Bridgelux 45ml Solar Charging Time: 6-7 Hours in Bright Sunlight Lighting Time: 12 hrs per Night 3 Rainy Days Backup

Electrical

Solar Panel: 70 watt Lithium Battery: 26AH, 12V

14.90

Working Temp: -30° C ~ 60° C

Material

Aluminum Alloy & PC Lens Size: 47' (1200 mm) x 12' (330 mm) x 5.5' (140 mm)

Waterproof: IP65

Components

Durable Light Quality Solar Panel Brackets 42 OPTO semi-conductors All air craft grade anodized Supports Solar Panel aluminum provide balanced light High diffusion plastic lens **Extruded Aluminum** Will never rust or get brittle like removes all hot spots Mill Finished steel or plastic No Harmful UV gets in Dimentions: 2'x2' Weather proof solar panel Wider spectrum Depth: 0.06" incandescent & flourscent lights Solar Panel Efficient **Control Remotely** 70 watt, proprietary, high Proprietary, high purity, purity, mono-crystalline Can be turned solar panel with high solar cells on and off by transparent low-iron Weather proof in most severe **FREE ENERGY** an app on your tempered glass conditions cellphone High transparent, low iron Powered by the sun tempered glass Built for maximum Free Energy performance and safety Installment Images BUIL



888-355-5786





solaroenergy.com

22955 McAuliffe Drive, Suite A • Robertsdale, AL 65767

<u>solaro</u>